

EXPLORER 710

High-Speed, Portable BGAN Terminal

October 2020 Product Sheet





Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



ecifications

Specifications	
Dimensions	
Total H / W / D:	332 / 279 / 54 mm
	13.07 / 10.98 / 2.13 inches
Total weight:	3.5 kg / 7.7 lbs (incl. battery)
Antenna:	1.9 kg / 4.2 lbs
Transceiver (incl. battery):	1.6 kg / 3.5 lbs

Global Services	
Voice:	4 kbps AMBE+2
Premium voice:	3.1 kHz audio, 64 kbps
Standard IP:	Up to 492 kbps
Streaming IP:	32, 64, 128 kbps
	(256 kbps & BGAN X-Stream)
HDR Streaming:	Min. 600 kbps
	Min. 300 kbps (Half-channel
HDR)	
ISDN:	UDI 64 kbps / RDI 56 kbps

,	
ISDN:	UDI 64 kbps / RDI 56 kbps
SMS:	Not supported
Inmarsat frequencies:	1518.0 - 1525.0 MHz (Rx) (EMEA)
	1525.0 - 1559.0 MHz (Rx)
	1626.5 - 1660.5 MHz (Tx)
	1668.0 - 1675.0 MHz (Tx) (EMEA)

EIRP:	20dBW ±1dB

PMOLED Display, 5 navigation keys User Interface: Audio and LCD pointing aids and LED

Languages: UK, FR, DE, ES, RU and CN

Inmarsat Class 1 Type Approval at launch Approvals: CE & FCC at launch. Other approvals TBC



Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Interfaces

2 x LAN (RJ-45) interface

Power over Ethernet: PoE Cl. 2 on one RJ-45 interface Max. cable length: 100m / 328ft (Cat5 UTP)

1 x USB host interface 2.0 (host), Charging up to 2A

1 x ISDN interface

RJ-45

Max. units per port: 8, max, total power supplied 1W

1 x Transceiver / Antenna interface Connector type:

Max. cable loss: 1.4 / 20dB @ 1.5GHz

1 x BGAN SIM-Card slots

WLAN Access Point

Standard: IEEE 802.11 b/g

Environmental conditions

Temperature	
Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F

Battery storage temperature 1 month: -20°C to +60°C / -4°F to +140°F

3 months: -20°C to +45°C / -4°F to +113°F 1 year: -20°C to +20°C / -4°F to +68°F

Water and dust: Transceiver: IP52 / Antenna: IP66 Relative humidity: 95% non-condensing at +40°C / +104°F

Power

DC input range: 10-32VDC

Power consumption

Intelligent Power Management 65W (max.)

AC/DC power supply

Input: 100-240VAC, 47-63Hz, 65W 19VDC Output:

Connector type: 2.5 / 5.5 mm power iack

Lithium ion, rechargeable Battery: Stand-by time: 2h30m @ 144 kbps Transmit time, max .:

(25°C / 77°F) 1h30m @ 650 kbps Receive time, max .: 3h30m @ 492 kbps

Subject to change without notice

COBHAM

Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

Other features

Built-in SIP server Embedded Webserver

Advanced Router with admin control

Wireless Access Point

Battery hot-swap and Built-in BGAN bonding Remote activation and remote management

EXPLORER Connect App for IOS and Android:

Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

EXPLORER Cellular Modem for USB:

With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all vour devices

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

403720B-100	EXPLORER 710 Antenna
403686G	Lithium Ion Battery
403720B-010	Battery Hot Swap Cable
403682P	100-240V AC/DC Power Supply
403650A-009	Car Charger Cable
403670A-00500	IP Handset incl. Cradle
403650A-921	Pole Mount Kit
403720B-942	10m Antenna Cable
403720B-945	30m Antenna Cable
403720B-947	50m Antenna Cable
403720B-953	80m Antenna Cable
403756A-0500	EXPLORER Cellular USB Modem

Product number

403720B-00500 **EXPLORER 710 Terminal**

For further information please contact:

Cobham SATCOM Lundtoftegaardsvej 93 D DK-2800 Kgs. Lyngby Denmark

Tel: +45 3955 8800